

Part Number: 120452E-LSOH-RED-305-01
Description: WEBNET Cat 6 U/UTP 4pair Low
 Smoke Non-Halogen (LSNH) Red



Product Construction

Conductor Material : Bare Copper
 Insulation Material : High Density Polyethylene (HDPE)
 Number of Pairs : 4
 Pair Colours : Blue, Blue/White; Orange, Orange/White,
 Green, Green/White; Brown, Brown/White
 Sheath Material : Low Smoke Non-Halogen (LSNH)
 Sheath Colour : Red



Mechanical Characteristics

Overall Diameter : 5.9mm ± 0.30mm
 Temperature Range : Fixed -10°C to +60°C Flexing 0°C to +50°C
 Bend Radius : 8 x Overall Diameter
 Weight : 40 kg/km

Electrical Characteristics

Max. Conductor DC Resistance : ≤ 9.5 Ω/km @ 20°C
 Max. Resistance Unbalanced : < 2.5%
 Max. Insulation Resistance : > 5000 MΩ x m
 Mutual Capacitance : < 5.6 nF/100m
 Capacitance Unbalanced : 1600 pF/km
 Impedance @ 100 MHz : 100 Ω ± 5
 Velocity of Propagation : 65 %
 Delay Skew : < 45 ns / 100m
 Dielectric Strength - DC : 1kV for 1minute

Frequency (MHz)	Attenuation (dB/100m)	NEXT (dB)	PS - NEXT (dB)	ACRF (dB)	PS-ACRF (dB)	Return Loss (dB)
1	≤ 2.0	≥ 74.3	≥ 72.3	≥ 67.8	≥ 64.8	20.0
4	≤ 3.8	≥ 65.3	≥ 63.3	≥ 55.8	≥ 52.8	23.0
8	≤ 5.3	≥ 60.8	≥ 58.8	≥ 49.7	≥ 46.7	24.5
10	≤ 6.0	≥ 59.3	≥ 57.3	≥ 47.8	≥ 44.8	25.0
16	≤ 7.6	≥ 56.2	≥ 54.2	≥ 43.7	≥ 40.7	25.0
20	≤ 8.5	≥ 54.8	≥ 52.8	≥ 41.8	≥ 38.8	25.0
25	≤ 9.5	≥ 53.3	≥ 51.3	≥ 39.8	≥ 36.8	24.3
31.25	≤ 10.7	≥ 51.9	≥ 49.9	≥ 37.9	≥ 34.9	23.6
62.5	≤ 15.4	≥ 47.4	≥ 45.4	≥ 31.9	≥ 28.9	21.5
100	≤ 19.8	≥ 44.3	≥ 42.3	≥ 27.8	≥ 24.8	20.1
200	≤ 29.0	≥ 39.8	≥ 37.8	≥ 21.8	≥ 18.8	18.0
250	≤ 32.8	≥ 38.3	≥ 36.3	≥ 19.8	≥ 16.8	17.3

Performance @ 20°

Certifications & Standards

Flame Retardancy : BS EN 60332-1-2 Certification : HDBaseT
 Low Smoke : BS EN 61034-2 RoHS 3 Compliant : Yes
 Halogen Gas : BS EN 60754-1&2 REACH Compliant : Yes
 Manufactured in Accordance to : TIA/EIA 568-C.2, IEC 11801 Class E, EN 50288-6-1, ISO/IEC 61156-5, EN 50173-1
 UKCA CPR Classification : Eca BS EN 50575:2014+A1:2016



Publication Date: 30/01/2023
 Revision Number: 2.0
 Written by: GB
 Authorised by: GB

Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK
 Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.