

Part Number: 590003D-LSNH-BLK

Description: WF100 75ohm Coax Low Smoke Non-Halogen (LSNH) Black – CAI Approved



**Product Construction**

Conductor Material	:	Plain Annealed Copper
Conductor Stranding	:	Solid, 1/1.00mm
Dielectric Material	:	Foam Polyethylene (FPE)
Dielectric Diameter	:	4.6mm ± 0.10
Screening 1	:	Overall Plain Copper Foil
Screening 1 Coverage	:	> 100%
Screening 2	:	Plain Copper Wire Braid
Screening 2 Coverage	:	> 55% ± 3
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	Black



**Mechanical Characteristics**

Overall Diameter	:	6.65mm ± 0.3mm
Temperature Range	Fixed	-15°C to +70°C
	Flexing	-5°C to +70°C
Bend Radius	:	10 x Overall Diameter
Weight	:	51 kg/km

**Electrical Characteristics**

Inner Conductor DC Resistance	:	≤ 26 Ω/km @ 20°C
Outer Conductor DC Resistance	:	≤ 15 Ω /km @ 20°C
Characteristic Impedance	:	75 Ω ± 3
Nominal Capacitance	:	54 pF/m ± 3
Velocity of Propagation	:	82%

**Attenuation @20°C**

Frequency (MHz)	Attenuation (per 100m)	Frequency (MHz)	Attenuation (per 100m)
5	≤ 1.6 dB	860	≤ 19.5 dB
50	≤ 4.6 dB	1000	≤ 21.5 dB
100	≤ 6.5 dB	1750	≤ 29.0 dB
200	≤ 9.5 dB	2150	≤ 32.5 dB
460	≤ 15.0 dB		

**Return Loss @ 20°C**

Frequency (MHz)	Return Loss
5MHz - 470MHz	≥ 23 dB
470MHz - 862MHz	≥ 20 dB
862MHz - 2150MHz	≥ 18 dB

**Certifications & Standards**

CAI Certification	:	CAI 0116F
Screening Class	:	BS EN 50117
Flame Retardancy	:	BS EN 60332-1-2
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Dca s2, d2, a1 to BS EN 50575:2014+A1:2016



Publication Date: 15/11/2022  
 Revision Number: 2.0  
 Written by: GB  
 Authorised by: GB

**Webro Cables & Connectors Ltd**

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK  
 Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | [www.webro.com](http://www.webro.com)

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.