



Part Number: 120571C-LSNH-WHT

Description: WEBNET Cat 6A 23awg 4pair U/FTP Low Smoke Non-Halogen (LSNH) White

Product Construction

Conductor Material	:	Bare Copper, Solid
Conductor Size	:	23(1)awg
Insulation Material	:	Skin/Foam/Skin Polyethylene (SFSPE)
Number of Pairs	:	4
Pair Colours	:	Blue/White; Orange/White; Green/White; Brown/White
Common Drain Wire	:	Tinned Copper, 1/0.4mm
Screening 1	:	Ind. Aluminium Foil Screened Pairs, ≥ 100% Coverage
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	White

Mechanical Characteristics

Overall Diameter	:	7.7mm ± 0.2mm
Temperature Range	:	Fixed -20°C to +70°C Flexing 0°C to +50°C
Bend Radius	:	Fixed 4 x Overall Diameter Flexing 8 x Overall Diameter
Weight	:	66 kg/km

Electrical Characteristics

Max. Conductor DC Resistance @ 20°C	:	≤ 9.5 Ω/km
Max. Resistance Unbalanced	:	< 2%
Max. Insulation Resistance	:	> 5000 MΩ x m
Mutual Capacitance	:	< 56 pF/m
Capacitance Unbalanced	:	1600 pF/km
Impedance @ 100 MHz	:	100 Ω ± 5
Velocity of Propagation	:	76 %
Delay Skew	:	< 25 ns / 100m
Voltage Rating	:	125V



Frequency (MHz)	Attenuation (dB/100m)	NEXT (dB)	PS – NEXT (dB)	ACR (dB/100m)	PS – ACR (dB/100)	ACRF (dB/100m)	PS-ACRF (dB/100m)	Return Loss (dB)
1	2.0	95	92	90	87	100	97	25
4	3.6	95	92	90	87	100	97	25
10	5.4	95	92	85	82	90	87	28
100	18.3	87	84	75	72	75	72	25
200	25.0	87	84	75	72	70	67	25
250	29.1	85	82	52	49	65	62	23
400	37.4	75	72	41	48	55	52	23
500	41.5	75	72	30	27	55	52	21

Performance @ 20°C

Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2	RoHS 3 Compliant	:	Yes
Low Smoke	:	BS EN 61034-2	REACH Compliant	:	Yes
Halogen Gas	:	BS EN 60754-1&2			
Manufactured in Accordance to	:	TIA/EIA 568-C.2, IEC 11801 Class Ea, EN 50288-4-1, ISO/IEC 61156-5, EN 50173-1			
CE CPR Classification	:	Cca s1a. d1. a1 to EN 50575:2014+A1:2016			



Publication Date: 07/04/2022
 Revision Number: 1.0
 Written by: GB
 Authorised by: GB

Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK

Tel: +44 (0)115 9724483 • Fax: +44 (0)115 9461230 • sales@webro.com • www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.